



"Leading the Way in Auger and Trencher Attachments."

## Auger Speed & Power Data

### Model SK225

All LOWE® hydraulic auger drive units are for use on hydraulic systems with ratings up to 3,200 PSI (22,063 ka). The SK250 and SK450 can be used with systems rated for use up to 4,500 PSI (31,023 ka)

SPEED		
GPM	Lpm	RPM
15	57	38
20	76	49
25	95	62
30	114	73

POWER		
Pressure	Theoretical Torque	Near Actual Torque
PSI	Lbs/ft	Lbs/ft
2,000	2,026	1,798
2,500	2,531	2,260
3,000	3,039	3,144
kPa	N.m	N.m
13,790	2,747	1,438
17,237	3,432	3,064
20,684	4,120	3,680

[SK-Series Specifications](#)

[SK-Series Auger Drives](#)

[XL-Series Auger Drives](#)

[E-Series Auger Drives](#)

[Hydraulic Augers](#)

[Home Page](#)

### Lowe Manufacturing Co., Inc.

**Mailing Address:**  
 P.O. Box 275  
 Readstown, WI 54652

**Shipping Address:**  
 18903 High Point Road  
 Viola, WI 54664

Toll Free: **1-888-DIG-LOV**  
 Fax: 1-608-538-3  
 E-mail: [Lowes@Lowes](mailto:Lowes@Lowes)

[View Map](#)

Copyright© - Lowe Manufacturing Co., Inc.