



"Leading the Way in Auger and Trencher Attachments."

Auger Speed & Power Data

Model SK225

All LOWE® hydraulic auger drive units are for use on hydraulic systems with ratings up to 3,200 PSI (22,063 ka). The SK250 and SK450 can be used with systems rated for use up to 4,500 PSI (31,023 ka)

| SPEED | | |
|-------|-----|-----|
| GPM | Lpm | RPM |
| 15 | 57 | 38 |
| 20 | 76 | 49 |
| 25 | 95 | 62 |
| 30 | 114 | 73 |

| POWER | | |
|----------|--------------------|--------------------|
| Pressure | Theoretical Torque | Near Actual Torque |
| PSI | Lbs/ft | Lbs/ft |
| 2,000 | 2,026 | 1,798 |
| 2,500 | 2,531 | 2,260 |
| 3,000 | 3,039 | 3,144 |
| kPa | N.m | N.m |
| 13,790 | 2,747 | 1,438 |
| 17,237 | 3,432 | 3,064 |
| 20,684 | 4,120 | 3,680 |

[SK-Series Specifications](#)

[SK-Series Auger Drives](#)

[XL-Series Auger Drives](#)

[E-Series Auger Drives](#)

[Hydraulic Augers](#)

[Home Page](#)

Lowe Manufacturing Co., Inc.

Mailing Address:
 P.O. Box 275
 Readstown, WI 54652

Shipping Address:
 18903 High Point Road
 Viola, WI 54664

Toll Free: **1-888-DIG-LOV**
 Fax: 1-608-538-3
 E-mail: Lowes@Lowes

[View Map](#)

Copyright© - Lowe Manufacturing Co., Inc.