



BOBCAT HAS THE RIGHT TOOL FOR THE JOB.

BOBCAT ATTACHMENTS

Trencher Attachment Specifications

[Back to Trencher](#)

	LT112	LT113	LT213	LT313	LT405	LT414	MX112
Operating Weight	615 lbs	615 lbs	725 lbs	955 lbs	1520 lbs	1255 lbs	570 lbs
Length	60.7 in	60.7 in	74 in	79.5 in	105 in	90 in	68.2 in
Width	36 in	36 in	56 in	56 in	65 in	56.25 in	N/A
Height	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Auger Diameter	12 in	12 in	12 in	12 in	19 in	14.25 in	12 in
Frame Width (std. equipment)	36 in	36 in	56 in	56 in	65 in	56.25 in	30.6 in
Maximum Operating Pressure	3000 psi	3000 psi	3300 psi	3300 psi	3300 psi	3300 psi	3000 psi
Side Shift Travel	16.1 in	16.1 in	23.1 in	21.3 in	26 in	21.8 in	16.1 in
Standard Boom Length	39.4 in	39.4 in	52.5 in	55.5 in	63 in	65 in	33.5 in
Dig Depth	2 ft	3 ft	3 ft	4 ft	4 ft	50 in	2 ft
Widths Available Min	4 in	4 in	4 in	6 in	6 in	6 in	4 in
Widths Available Max	8 in	8 in	8 in	12 in	12 in	12 in	8 in

Compatible Carriers for Bobcat Trenchers

	LT112 Trencher	LT113 Trencher	LT213 Trencher	LT313 Trencher	LT405 Trencher	LT414 Trencher	MX112 Trencher
All-Wheel Steer Loaders				A300	A300	A300	
			T110 T140	T140 T180 T190 T630	T180 T190 T250 T250 (RS)	T180 T190 T250 T250 (RS)	