

Indirect Fired Heaters

DEPENDABLE HEAT When and Where you Need it

- Indirect fired heat exchanger allows external exhaust of combustion products
- Heavy duty pneumatic tires and slim design provides for easy site mobility and transportation
- Choose from heating oil, diesel, kerosene, propane or natural gas
- Low current draw-only 6 amps
- FVO-200 model has a built in fuel tank and gauge
- Steel frame for stacking during transportation or storage



FVO-200



FVP-200

flagro™
USA INC.

Indirect Fired Heaters

OIL, NATURAL GAS, PROPANE

Model:	FVO-200 Oil	FVN-200 Natural Gas	FVP-200 Propane
Heat Capacity	200,000 BTU's	200,000 BTU's	200,000 BTU's
Fuel Tank Capacity	23 US Gallons	External N/A	External N/A
Operation Time/ Fuel consumption	15 Hours 1.5 Gallons/Hour	190 CFH	9.25 LBS/HR
Dimensions	51 1/2" L 27" W 43 1/2" H	53 1/2" L 27" W 39 1/2" H	53 1/2" L 27" W 39 1/2" H
Heat Exchanger	16 Gauge	16 Gauge	16 Gauge
Fan Motor	1/2 HP @1725 RPM 1500 CFM	1/2 HP @1725 RPM 1500 CFM	1/2 HP @1725 RPM 1500 CFM
Ignition	Direct Spark Igniter	Direct Spark Igniter	Direct Spark Igniter
Nozzle Size/Gas Pressure	1.25 X 60B @145 PSI	3.5" W.C.	3.5" W.C.
Air Outlet	One 12 Inch Diameter	One 12 Inch Diameter	One 12 Inch Diameter
Wheels	Two 12" Pneumatic/ Two 6" swivel lockable Caster	Two 12" Pneumatic/ Two 6" swivel lockable Caster	Two 12" Pneumatic/ Two 6" swivel lockable Caster
Power Supply	115 Volts, 15 Amps	115 Volts, 15 Amps	115 Volts, 15 Amps
Approvals	cETLus	cETLus	cETLus
Weight	330 LBS.	280 LBS.	280 LBS.

Both the oil-fired and fuel units include:

- Stackable frame for easy storage
- 16 gauge 304 Stainless steel welded heat exchanger
- 1500 CFM Blower
- 170 Degree F outlet temperature rise
- Proven Riello burner technology
- ETL approval for use in the United States and Canada

Other options available:

- 12 in. x12 ft. Flexible Ducting
- Remote Thermostat Control with 25 ft. cord

14501 Judicial Road, Suite 40
Burnsville, MN 55306
TEL: (952) 898-2881 (866) 266-2484
FAX: (952) 898-6693 E-MAIL: info@flagrousa.com
www.flagrousa.com

