

5.3 Specifications

Machine Specifications

	SPECIFICATION	M20
	Platform Capacity	350 lbs (159 kg)
	Power Source	AC or DC Drill
	Rated Horizontal Force	52.5 lbs (234 N)
	Machine Weight	278 lbs (126 kg)
	Swivel / Lockable Caster Diameter	5 in (127 mm)
	Platform Size (L x W)	26 in x 30 in (660 mm x 762 mm)
	Mast Section Weight	20.7 lbs (9.4 kg)
	Rear Outrigger Weight	7.8 lbs (3.6 kg)
	Front Outrigger Weight	10.3 lbs (4.7 kg)
	Flat Free Transport Wheels	12 in x 3.5 in (305 mm x 89 mm)
	Drive	Worm Drive with Integrated Drive Gear & Brake
A	Stowed Length	53 in (1346 mm)
B	Stowed Width	30 in (762 mm)
C	Stowed Height	56.6 in (1741 mm)
D	Minimum Platform Height	12.9 in (329 mm)
E	Outrigger Footprint Width	52.1 in (1324 mm)
F	Outrigger Footprint Length	58.9 in (1496 mm)
G	Distance from Wall Side	11 in (281mm)
H	Distance from Wall Front	12.3 in (314 mm)
I	Erected Mast Height	16.3 ft (5.0 m)
J	Max Platform Height	14.3 in (4.34 m)
	Max Working Height*	20.3 ft (6.19 m)

Table 5-2 Machine Specifications

* Based on Platform Height plus 2 m

Figure 5-5 Machine Specifications

